

# TORIDAS MARK III



Automated chicken whole leg  
deboning machine



*“Delivering benefits through  
dialogues and technology”*



### Description

**TORIDAS** automatically separates bone and deboned meat with high quality and high yield under hygienic operation.

**TORIDAS MARK III** maintains the same meat quality as when processed with the **MARK II**, while increasing capacity and yield to achieve further efficiency.

This new system offers a higher working speed of up to 1,500 whole-legs per hour, ensuring enhanced efficiency and productivity. Equipped with an innovative whole-leg clamping system and a flexible cutting mechanism, it delivers superior performance and adaptability. The system features integrated blade change control, a reduced footprint, and minimal maintenance requirements. Its compact design makes it ideal for space-conscious setups.

## Features

### Optimal cut based on size

Two-step measurement function for the total length of the whole leg and the knee joint position enables cutting at the optimum position every time.

Improved final separation of bone and meat allows for even higher yields.

### Optimal adjustment, easy maintenance

Improved maintainability by facilitating cut adjustment and reducing the number of parts to be replaced, based on experience with the Mark II.

### Replaceable from conventional Mark II

The outer dimensions of the unit are equivalent to those of the Mark II, making it easily adaptable for renewal or combined use.


No major line modifications required.

### Hygienic in processing and internal construction

No human intervention is required except when loading whole leg, which allows for hygienic processing.

The inside of the machine can be washed with hot water and sterilized with chemicals.


### Processing image - Outer dimensions



Input



Output



### Specifications

|                          |                                                                                                                              |                                                                                 |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|
| Capacity                 | 1,500 legs/hour, maximum                                                                                                     |                                                                                 |
| Model                    | MT-05                                                                                                                        |                                                                                 |
| Applicable raw materials | Chicken whole leg (250~550g or 0.55~1.21lbs/leg)                                                                             |                                                                                 |
| Standard dimensions      | 1,330mm(L) x 1,430mm(W) x 2,924mm(H) [52.3in(L) x 56.2in(W) x 115.1in(H)] *Height may vary depending on the site conditions. |                                                                                 |
| Weight                   | 2,300kg(5,071lbs)                                                                                                            |                                                                                 |
| Utility                  | Electricity                                                                                                                  | 3φ 200V 6kW                                                                     |
|                          | Water supply                                                                                                                 | 0.15MPa (21.8PSI) 0.5ℓ/min (0.02CFM)                                            |
|                          | Compressed air                                                                                                               | 0.5MPa (72.5PSI) 500ℓ/min (17.6CFM)                                             |
| Options                  | Auto-loading system                                                                                                          | Dedicated automated deboning specifications for layer and other special chicken |
|                          | TORIDAS monitoring system                                                                                                    | Pre-wash equipment and CIP                                                      |
|                          | Circular cutter sharpener                                                                                                    | Straight cutter sharpener                                                       |

# Sales Offices

EMEA



## DUBAI

☎ +971 4 8886363 | Fax +971 4 8886373  
✉ mmesales@mayekawa.ae  
📍 P.O. Box 61349, W-HOUSE No. RA-08-UC05  
Jebel Ali Free Zone Dubai, UAE

## SPAIN

☎ +34 91 8300392 | Fax +34 91 8300397  
✉ mayekawa@mayekawa.es  
📍 Calle Montevideo 5, Nave 13 Pol. Industrial  
Camporroso 28806, Madrid

## FRANCE

☎ +33 1 30 58 97 95  
✉ contact-mef@mayekawa.fr  
📍 20 rue Ampère,  
22 590 Pordic

## TURKEY

☎ +90 212 46536 31- 34 | Fax +90 212 4653635  
✉ info@mayekawa.eu  
📍 Dünya Ticaret MerkeziA/2 Blok Kat: 10  
No. 325 Yeşilköy, Istanbul

## GERMANY

☎ +49 5426 2989920  
✉ info@mayekawa.de  
📍 Zum Buckesch 7a  
48336 Sassenberg, Deutschland

## UKRAINE

☎ +38 (044) 251-46-62  
✉ info@mayekawa.ua  
📍 Golosiivska Street 17 Office 110  
03039 Kiev

## HUNGARY

☎ +36 23 502 152  
✉ hungary@mayekawa.hu  
📍 H-2040 Budaörs,  
Gyár u.2.

## UNITED KINGDOM

☎ +44 0141 737 6139  
✉ accounts@mayekawa.uk  
📍 5th Floor, The Wheatsheaf Building,  
52 Speirs Wharf, Glasgow, G4 9TJ

## ITALY

Milano office:  
☎ +39 02 4892 9218 | Fax +39 02 4531 728  
📍 Via Riccardo Lombardi 19/12  
20153 Milano  
Bologne office:  
☎ +39 051 726 364 | Fax +39 051 726 804  
📍 Via Pradazzo 7  
40012 Calderara di Reno, Bologne  
✉ standard-package@mayekawa.it

## GLOBAL HEAD OFFICE – MAYEKAWA JAPAN

☎ 81 3 3642 8181 | Fax 81 3 3643 7094  
✉ e-public@mayekawa.co.jp  
📍 3-14-15 Botan Koto-ku  
Tokyo 135 8482, JAPAN

## POLAND

☎ +48 61 8420738 | Fax +48 61 8485837  
✉ biuro@mayekawa.pl  
📍 ul. Druskiennicka 8/10  
60-476 Poznan

## EMEA HEAD OFFICE – MAYEKAWA EUROPE

☎ +33 1 30 58 97 95  
✉ das@mayekawa.eu  
📍 Leuvensesteenweg 605  
1930 Zaventem - Belgium

Follow us as  
Mayekawa Europe on:



Visit our  
website

